



SNR BEARING CORP.OF AMERICA



skf SSAFS 22534 x 6 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22534 x 6 T

SSAFS 22534 x 6 T Bearing 2D drawings and 3D CAD models

d_a	152.4 mm
D_a	309.999 mm
C_a	95.809 mm
A_1	171.45 mm
A_2	309.575 mm
S	4.763 mm
b_a	74.612 mm
H	360.363 mm
H_1	179.4 mm
H_2	69.85 mm
L	628.65 mm
R_1	115.888 mm
R_2	37.306 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	54.769 mm
Housing	SSAFS 534
Bearing	22234 CCK/W33
Adapter sleeve assembly	SNW 34x6
Stabilizing ring	SR-34-0
Taconite seal	TER 141
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	520 r/min
P_{60°	345 kN
P_{90°	207 kN



SNR BEARING CORP.OF AMERICA

P _{120 °}	127 kN
P _{150 °}	113 kN
P _{180 °}	133 kN
P _a	43.6 kN
Mass pillow block	168 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	878.85 g