




SNR BEARING CORP.OF AMERICA



skf FSAF 23024 KATLC x 4.1/8 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 23024 KATLC x 4.1/8

FSAF 23024 KATLC x 4.1/8 Bearing 2D drawings and 3D CAD models

d_a	104.775 mm
D_a	180 mm
C_a	55.804 mm
A_1	111.125 mm
A_2	155.575 mm
b_a	46.831 mm
H	217.488 mm
H_1	114.3 mm
H_2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J_1	60.325 mm
L	387.35 mm
N_1	22.225 mm
R_1	58.737 mm
R_2	30.163 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	39.688 mm
Housing	FSAF 024 KA
Stabilizing ring	2 x 38151-24
Labyrinth ring	2 x LOR 112
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac	1350 r/min



SNR BEARING CORP.OF AMERICA

Plus seal	
P ₆₀ °	119 kN
P ₉₀ °	71.2 kN
P ₁₂₀ °	44.5 kN
P ₁₅₀ °	40 kN
P ₁₈₀ °	48.9 kN
P _a	16.7 kN
Mass pillow block	28.6 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g