




# SNR BEARING CORP.OF AMERICA



skf SAF 1516 x 2.5/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1516 x 2.5/8 T

SAF 1516 x 2.5/8 T Bearing 2D drawings and 3D CAD models

$d_a$	66.675 mm
$D_a$	140 mm
$C_a$	42.799 mm
$A_1$	88.9 mm
$A_2$	209.55 mm
$b_a$	30.163 mm
H	169.863 mm
$H_1$	88.9 mm
$H_2$	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
$N_1$	22.225 mm
$R_1$	53.181 mm
$R_2$	21.431 mm
$R_G$	3/8 NPT
$P_G$	1/8 NPT
h	49.212 mm
Housing	SAF 516
Bearing	1216 K
Adapter sleeve assembly	SNW 16x2.5/8
Stabilizing ring	2 x SR-1516
Taconite seal	TER 43
End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	1150 r/min



## SNR BEARING CORP.OF AMERICA

P <sub>60°</sub>	83.2 kN
P <sub>90°</sub>	49.8 kN
P <sub>120°</sub>	30.2 kN
P <sub>150°</sub>	26.7 kN
P <sub>180°</sub>	31.6 kN
P <sub>a</sub>	6.23 kN
Mass pillow block	16.4 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g