




SNR BEARING CORP.OF AMERICA



skf SAFS 22518 x 3.1/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22518 x 3.1/8 T

SAFS 22518 x 3.1/8 T Bearing 2D drawings and 3D CAD models

d_a	79.375 mm
D_a	160 mm
C_a	49.809 mm
A_1	98.425 mm
A_2	206.375 mm
S	4.763 mm
b_a	40.481 mm
H	196.85 mm
H_1	101.6 mm
H_2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
L	349.25 mm
N_1	23.813 mm
R_1	60.325 mm
R_2	27.781 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	38.1 mm
Housing	SAFS 518
Bearing	22218 EK
Adapter sleeve assembly	SNW 18x3.1/8
Stabilizing ring	SR-18-15
Taconite seal	TER 189
End plug (suffix Y)	EPR 11



SNR BEARING CORP.OF AMERICA

Max. speed for Taconite seal	950 r/min
P _{60°}	141 kN
P _{90°}	84.5 kN
P _{120°}	53.4 kN
P _{150°}	48 kN
P _{180°}	58.7 kN
P _a	10.9 kN
Mass pillow block	30.8 kg
Cap bolt	1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	141.75 g