



SNR BEARING CORP.OF AMERICA



skf SAW 23526 x 4.5/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23526 x 4.5/16

SAW 23526 x 4.5/16 Bearing 2D drawings and 3D CAD models

d_a	109.537 mm
D_a	230 mm
C_a	89.789 mm
A_1	133.35 mm
A_2	193.675 mm
S	4.763 mm
b_a	65.881 mm
H	295.275 mm
H_1	152.4 mm
H_2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J_1	82.55 mm
L	466.725 mm
N_1	25.4 mm
R_1	79.375 mm
R_2	36.513 mm
R_G	1/2 NPT
P_G	1/4 NPT
h	60.325 mm
Housing	SAW 526
Stabilizing ring	SR-26-0
Labyrinth ring	2 x LOR 115
End plug (suffix Y)	EPR 15
Bearing limiting speed	2600 r/min



SNR BEARING CORP.OF AMERICA

P _{60°}	189 kN
P _{90°}	113 kN
P _{120°}	73.8 kN
P _{150°}	68.1 kN
P _{180°}	84.5 kN
P _a	31.2 kN
Mass pillow block	68 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N · m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g