



# SNR BEARING CORP.OF AMERICA



skf FSAF 1617 x 2.13/16 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 1617 x 2.13/16 T

FSAF 1617 x 2.13/16 T Bearing 2D drawings and 3D CAD models

$d_a$	71.438 mm
$D_a$	180 mm
$C_a$	69.799 mm
$A_1$	111.125 mm
$A_2$	231.775 mm
$b_a$	52.388 mm
H	222.25 mm
$H_1$	114.3 mm
$H_2$	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
$J_1$	60.325 mm
L	387.35 mm
$N_1$	22.225 mm
$R_1$	66.675 mm
$R_2$	30.163 mm
$R_G$	3/8 NPT
$P_G$	1/4 NPT
h	47.625 mm
Housing	FSAF 617
Stabilizing ring	2 x SR-1617
Taconite seal	TER 182
End plug (suffix Y)	EPR 10
Max. speed for Taconite seal	1050 r/min
$P_{60^\circ}$	104 kN



## SNR BEARING CORP.OF AMERICA

P <sub>90 °</sub>	62.3 kN
P <sub>120 °</sub>	39.1 kN
P <sub>150 °</sub>	35.6 kN
P <sub>180 °</sub>	42.9 kN
P <sub>a</sub>	10.5 kN
Mass pillow block	25.5 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	365.71 g