



SNR BEARING CORP.OF AMERICA



skf SAF 1613 x 2.1/4 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1613 x 2.1/4 TLC

SAF 1613 x 2.1/4 TLC Bearing 2D drawings and 3D CAD models

d_a	57.15 mm
D_a	140 mm
C_a	57.785 mm
A_1	88.9 mm
A_2	134.938 mm
b_a	32.544 mm
H	167.481 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N_1	22.225 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	36.513 mm
Housing	SAF 613
Stabilizing ring	2 x SR-1613
Labyrinth ring	2 x LOR 33
PosiTrac Plus contact element	2 x B10724-32
End plug (suffix Y)	EPR 7
Max. speed for PosiTrac Plus seal	2600 r/min



SNR BEARING CORP.OF AMERICA

P _{60°}	83.2 kN
P _{90°}	49.8 kN
P _{120°}	30.2 kN
P _{150°}	26.7 kN
P _{180°}	31.6 kN
P _a	6.49 kN
Mass pillow block	17.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g