




SNR BEARING CORP.OF AMERICA



skf SAF 1610 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1610 T

SAF 1610 T Bearing 2D drawings and 3D CAD models

d_a	42.862 mm
D_a	110 mm
C_a	50.8 mm
A_1	69.85 mm
A_2	190.5 mm
b_a	27.781 mm
H	147.637 mm
H_1	76.2 mm
H_2	28.575 mm
J min.	196.85 mm
J max.	228.6 mm
L	269.875 mm
N_1	19.05 mm
R_1	42.862 mm
R_2	19.05 mm
R_G	1/8 NPT
P_G	1/8 NPT
h	36.513 mm
Housing	SAF 610
Bearing	1310 EKTN9
Adapter sleeve assembly	SNW 10x1.11/16
Stabilizing ring	2 x SR-1610
Taconite seal	TER 20
End plug (suffix Y)	EPR 4
Max. speed for Taconite seal	1800 r/min



SNR BEARING CORP.OF AMERICA

P _{60°}	39.1 kN
P _{90°}	23.6 kN
P _{120°}	14.2 kN
P _{150°}	12.9 kN
P _{180°}	15.6 kN
P _a	4.07 kN
Mass pillow block	10 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	107.73 g