



SNR BEARING CORP.OF AMERICA



40 mm x 80 mm x 18 mm skf 7208 BEGAP
Single row angular contact ball bearings

Bearing No. 7208 BEGAP

7208 BEGAP Bearing 2D drawings and 3D CAD models

Size	80x40x18 mm
Bore Diameter	80 mm
Outer Diameter	40 mm
Width	18 mm
d	40 mm
D	80 mm
B	18 mm
d ₁	56.25 mm
d ₂	48.08 mm
D ₁	65.55 mm
a	34 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
d _a - min.	47 mm
D _a - max.	73 mm
D _b - max.	75.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	36.5 kN
Basic static load rating - C ₀	26 kN
Fatigue load limit - P _u	1.1 kN
Reference speed	11000 r/min
Limiting speed	11000 r/min
Calculation factor - k _r	0.095



SNR BEARING CORP.OF AMERICA

Calculation factor - k_a	1.4
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.36
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Light
Mounting Arrangement	Universal
Inch - Metric	Metric



SNR BEARING CORP.OF AMERICA

Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7208 BEGAP
Weight / LBS	0.785
Bore	1.575 Inch 40 Millimeter
Width	0.709 Inch 18 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
bore diameter:	40 mm
radial static load capacity:	26 kN
outside diameter:	80 mm
cage material:	Nylon
overall width:	18 mm
outer ring width:	18 mm
contact angle:	40 °
maximum rpm:	11000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	36.5 kN



SNR BEARING CORP.OF AMERICA

series:	72
d_1	56.25 mm
d_2	48.08 mm
D_1	65.55 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	47 mm
D_a max.	73 mm
D_b max.	75.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	36.5 kN
Basic static load rating C_0	26 kN
Fatigue load limit P_u	1.1 kN
Calculation factor A	0.0102
Calculation factor k_r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.37 kg