



SNR BEARING CORP.OF AMERICA



80 mm x 140 mm x 26 mm skf 7216 BEGAPH
Single row angular contact ball bearings

Bearing No. 7216 BEGAPH

7216 BEGAPH Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|---|
| Category | Angular Contact Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | Yes |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | PEEK |
| Contact Angle | 40 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Preload | Light |
| Mounting Arrangement | Universal |
| Inch - Metric | Metric |
| Long Description | 80MM Bore; 140MM Outside Diameter; 26MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap |



SNR BEARING CORP.OF AMERICA

| | |
|---|--|
| | Ring; C0-Medium; PEEK Cage; 40 Degree; 1 (Single); L |
| Category | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer URL | http://www.skf.com |
| d | 3.15 Inch 80 Millimeter |
| D | 5.512 Inch 140 Millimeter |
| B | 1.024 Inch 26 Millimeter |
| d | 80 mm |
| D | 140 mm |
| B | 26 mm |
| d ₁ | 103.55 mm |
| d ₂ | 91.44 mm |
| D ₁ | 117.85 mm |
| a | 59 mm |
| r _{1,2} min. | 2 mm |
| r _{3,4} min. | 1 mm |
| d _a min. | 91 mm |
| D _a max. | 130 mm |
| D _b max. | 134 mm |
| r _a max. | 2 mm |
| r _b max. | 1 mm |
| Basic dynamic load rating C | 85 kN |
| Basic static load rating C ₀ | 75 kN |
| Fatigue load limit P _u | 3.05 kN |
| Reference speed | 5600 r/min |
| Limiting speed | 5600 r/min |
| Calculation factor A | 0.0801 |
| | |



SNR BEARING CORP.OF AMERICA

| | |
|--------------------------|---------|
| Calculation factor k_r | 0.095 |
| Calculation factor e | 1.14 |
| Calculation factor X | 0.35 |
| Calculation factor Y_0 | 0.26 |
| Calculation factor Y_2 | 0.57 |
| Calculation factor X | 0.57 |
| Calculation factor Y_0 | 0.52 |
| Calculation factor Y_1 | 0.55 |
| Calculation factor Y_2 | 0.93 |
| Mass bearing | 1.45 kg |