



SNR BEARING CORP.OF AMERICA



25,4 mm x 63,5 mm x 20,638 mm NTN
4T-15100S/15250X Single row tapered roller
bearings

Bearing No. 4T-15100S/15250X

4T-15100S/15250X Bearing 2D drawings and 3D CAD
models

| | |
|------------------------------------|---------------------|
| Size | 25.4x63.5x20.638 mm |
| Bore Diameter | 25,4 mm |
| Outer Diameter | 63,5 mm |
| Width | 20,638 mm |
| d | 25,4 mm |
| D | 63,5 mm |
| T | 20,638 mm |
| B | 20,638 mm |
| C | 15,875 mm |
| a | 26.6 mm |
| rs min | 1.3 mm |
| r1s min | 1.5 mm |
| e | 0.35 |
| Y2 | 1.71 |
| Y0 | 0.94 |
| Mass | 0.32 kg |
| Dynamic load, C | 46.5 kN |
| Rating life coefficient, A2 | 1.4 |
| Static load, C0 | 54 kN |
| Nlim (oil) | 8,200 rpm |
| Nlim (grease) | 6,100 rpm |
| Min operating temperature, Tmin | -40 ° C |
| Max operating temperature, Tmax | 120 ° C |
| | |



SNR BEARING CORP.OF AMERICA

| | |
|----------------------|----------|
| ra max | 1.3 mm |
| r1a max | 1.5 mm |
| Category | Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.328 |
| Product Group | B04334 |