




SNR BEARING CORP.OF AMERICA



28,575 mm x 63,5 mm x 20,638 mm NTN
4T-15112/15250 Single row tapered roller bearings

Bearing No. 4T-15112/15250

4T-15112/15250 Bearing 2D drawings and 3D CAD models

Size	28.575x63.5x20.638 mm
Bore Diameter	28,575 mm
Outer Diameter	63,5 mm
Width	20,638 mm
d	28,575 mm
D	63,5 mm
T	20,638 mm
B	20,638 mm
C	15,875 mm
a	14.6 mm
rs min	3.5 mm
r1s min	1.3 mm
e	0.35
Y2	1.71
Y0	0.94
Mass	0.3 kg
Dynamic load, C	46.5 kN
Rating life coefficient, A2	1.4
Static load, C0	54 kN
Nlim (oil)	8,200 rpm
Nlim (grease)	6,100 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.42 Hz



SNR BEARING CORP.OF AMERICA

frequency, FTF	
Characteristic rolling element frequency, BSF	6.16 Hz
Characteristic outer ring frequency, BPF0	7.19 Hz
Characteristic inner ring frequency, BRFI	9.81 Hz
ra max	3.5 mm
r1a max	1.3 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.317
Product Group	B04334