




SNR BEARING CORP.OF AMERICA

38,1 mm x 72,238 mm x 20,638 mm NTN
4T-16150/16284 Single row tapered roller bearings



Bearing No. 4T-16150/16284

4T-16150/16284 Bearing 2D drawings and 3D CAD models

Size	38.1x72.238x20.638 mm
Bore Diameter	38,1 mm
Outer Diameter	72,238 mm
Width	20,638 mm
d	38,1 mm
D	72,238 mm
T	20,638 mm
B	20,638 mm
C	15,875 mm
d1	54 mm
a	16.44 mm
e	0.4
Y2	1.49
Y0	0.82
Mass	0.36 kg
Dynamic load, C	48 kN
Rating life coefficient, A2	1.4
Static load, C0	58.5 kN
Fatigue limit load, Cu	7.1 kN
Nlim (oil)	7,000 rpm
Nlim (grease)	5,300 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.43 Hz



SNR BEARING CORP.OF AMERICA

frequency, FTF	
Characteristic rolling element frequency, BSF	7.23 Hz
Characteristic outer ring frequency, BPF0	7.82 Hz
Characteristic inner ring frequency, BPF1	10.18 Hz
ra max	3.5 mm
r1a max	1.3 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.361
Product Group	B04334