



SNR BEARING CORP.OF AMERICA

NTN 4T-21075 Single row tapered roller bearings

Bearing No. 4T-21075

| | |
|---|-----------------|
| d | 19.05 mm |
| B | 21.84 mm |
| d1 | 36.2 mm |
| e | 0.59 |
| Y2 | 1.02 |
| Y0 | 0.56 |
| Dynamic load, C | 40 kN |
| Rating life coefficient, A2 | 1.4 |
| Static load, C0 | 39 kN |
| Fatigue limit load, Cu | 4.75 kN |
| Nlim (oil) | 11,000 rpm |
| Nlim (grease) | 8,000 rpm |
| Min operating temperature, Tmin | -40 ° C |
| Max operating temperature, Tmax | 120 ° C |
| Characteristic cage frequency, FTF | 0.39 Hz |
| Characteristic rolling element frequency, BSF | 4.14 Hz |
| Characteristic outer ring frequency, BPF0 | 4.32 Hz |
| Characteristic inner ring frequency, BPF1 | 6.68 Hz |
| ra max | 1.5 mm |
| Category | Roller Bearings |
| Inventory | 20.0 |
| | |

4T-21075 Bearing 2D drawings and 3D CAD models



SNR BEARING CORP.OF AMERICA

| | |
|----------------------|---------------|
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4547359518030 |
| Product Group | B04334 |